

GR SLING & U PANEL BAGS:

Unique characteristics:

- Ideal, cost effective, economical and highly feasible source for packaging of free flowing material in the granular, powder or crumble form.
 - Very easy to store and handle the Sling & U Panel Bags with a standard equipment.
 - Bulk bags when not in use could be easily folded and requires very less space in comparison to the storage of empty fiber drums and other containers used for packaging.
 - Sling & U Panel Bags once packed and filled with material do not require any additional packaging.
 - FIBCs are packed flat and square bale delivered to end users.
- Depending upon the bulk capacity of the product and its application, the FIBCs/Sling & U Panel bag comes with the guarantee of the Safe Factor of 5:1

TECHNICAL DETAILS:



Bag Type	SLING BAG / U PANEL
Bag Size	As per Customer Requirement
SWL	From 500 Kgs To 2000 Kgs
Safety Factor	5 : 1 Single Trip
Fabric	UV Stabilized polypropylene fabric GSM as per customer requirement.
Lifting Loop	As per customer requirement
Top Panel	As per Customer Requirement
Bag Weight	As per Bag Construction.

APPLICATION:

- Used in Packing / Construction related items like cement, sand and granite.
- Petrochemical & Chemical Industry for storing Granules & other raw materials.
- Agricultural related products like fertilizers, animal feed & grass.
- Industrial applications like scrap materials, copper coils & slag, sludge waste
- Used in Transport for storing Non –flammable dry substance.
- Food Industry like sugar, flour, spices, wheat, milk powder.
- Pharmaceutical industry.

