

File Name: cadillac xts manual pdf.pdf

Size: 2386 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 1 May 2019, 21:33 PM

Rating: 4.6/5 from 802 votes.

Status: AVAILABLE

Last checked: 5 Minutes ago!

In order to read or download cadillac xts manual pdf ebook, you need to create a FREE account.

[**Download Now!**](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:


We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with cadillac xts manual pdf . To get started finding cadillac xts manual pdf , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

cadillac xts manual pdf

2014 Cadillac XTS Owner Manual 

| | | | | | |
|-----------------------------------|------|--|------|---------------------------------|------|
| In Brief | 1-1 | Storage | 4-1 | Climate Controls | 8-1 |
| Instrument Panel | 1-2 | Storage Compartments | 4-1 | Climate Control Systems | 8-1 |
| Initial Drive Information | 1-4 | Additional Storage Features | 4-4 | Air Vents | 8-8 |
| Vehicle Features | 1-14 | Instruments and Controls | 5-1 | Maintenance | 9-9 |
| Performance and Maintenance | 1-19 | Controls | 5-2 | Driving and Operating | 9-1 |
| Keys, Doors, and Windows | 2-1 | Warning Lights, Gauges, and Indicators | 5-9 | Driving Information | 9-2 |
| Keys and Locks | 2-2 | Information Displays | 5-30 | Starting and Operating | 9-15 |
| Doors | 2-14 | Vehicle Messages | 5-36 | Engine Exhaust | 9-22 |
| Vehicle Security | 2-16 | Vehicle Personalization | 5-48 | Automatic Transmission | 9-23 |
| Exterior Mirrors | 2-19 | Universal Remote System | 5-53 | Drive Systems | 9-25 |
| Interior Mirrors | 2-20 | Lighting | 6-1 | Brakes | 9-26 |
| Windows | 2-21 | Exterior Lighting | 6-1 | Ride Control Systems | 9-29 |
| Roof | 2-25 | Interior Lighting | 6-6 | Cruise Control | 9-32 |
| Seats and Restraints | 3-1 | Lighting Features | 6-8 | Driver Assistance Systems | 9-43 |
| Head Restraints | 3-2 | Infotainment System | 7-1 | Fuel | 9-58 |
| Front Seats | 3-4 | Introduction | 7-1 | Trailer Towing | 9-62 |
| Rear Seats | 3-10 | | | Conversions and Add-Ons | 9-68 |
| Safety Belts | 3-13 | | | | |
| Airbag System | 3-22 | | | | |
| Child Restraints | 3-36 | | | | |

It is an text. For more LATCH System Child information on the symbol, refer to Restraints the Index. Box on page 42. 14. Horn on page 53. Instrument Panel Illumination Parking Assist Button. Press and Information If equipped with remote start, the hold for three seconds to sound the engine can be started from outside panic alarm. Press again or start the This section provides a brief of the vehicle. See Remote Keyless Entry RKE System Operation on To cancel a remote start, do any of page 23. the following Trunk Press and hold until the parking lamps turn off. Turn on the hazard warning flashers. Pull the switch up to front of the control up or down. raise it. Raise or lower the seat by See Power Windows on page 221. The driver support. With each press of and Power Seat Adjustment on Seats the button, the seat will change to page 34. the next lower setting, and then to Safety Belts the off setting. These lamps console.INT Move the lever up to INT for intermittent wipes, then turn the INT band up for more frequent wipes or down for less frequent wipes. If equipped, the controls are Climate Control System on page 86 on the back of the steering wheel. If Equipped. Press to mute or unmute the infotainment Steering Wheel Controls Press to go to the next or system when not on a call. Press to go back to the Rear Vision If equipped, LDW is intended to help previous menu. Parking Assist system, a higher Braking System speed Backing Warning System, Lift the cover to access the and the Rear Automatic Braking If the vehicle has Adaptive Cruise accessory power outlet. Press the before attempting to program the rear of again to open the Universal Remote system. Because sunroof fully. If the sunshade is not of the steps involved, it may be fully open when the comfort feature helpful to have another person is pressed the second time, the <https://www.cmevalves.com/userfiles/dgs-1224t-manual.xml>

- **cadillac xts manual pdf, 2018 cadillac xts owner s manual pdf, 2016 cadillac xts owner s manual pdf, 2014 cadillac xts owner s manual pdf, 2017 cadillac xts owner s manual pdf, 2013 cadillac xts owner s manual pdf, 2019 cadillac xts owner s manual pdf, 2015 cadillac xts owner s manual pdf, cadillac xts manual pdf, cadillac xts manual pdf, cadillac xts manual pdf 2017, cadillac xts owners manual pdf, 2016 cadillac xts manual pdf, 2014 cadillac xts manual pdf, 2014 cadillac xts owners manual pdf.**

Canceling a Remote Start

To cancel a remote start, do any of the following:

- Press and hold until the parking lamps turn off.
- Turn on the hazard warning flashers.
- Turn the vehicle on and then off. See Remote Vehicle Start on page 2-9.

Door Locks

To lock or unlock a door manually:

- Use the key in the driver door. The key cylinder is covered by a cap. See Door Locks on page 2-10.
- From the inside, to lock a door push down on the door lock knob on top of the door. To unlock a door, pull once on the door handle to unlock it, and again to open it.

Power Door Locks

From the inside, press or on the RKE transmitter. See Remote Keyless Entry (RKE) System Operation on page 2-3.

From the outside, if the vehicle is equipped with Keyless Access, press the button on the door handle when the Remote Keyless Entry (RKE) transmitter is within range to

unlock it. See Remote Keyless Entry (RKE) System Operation on page 2-3.

Trunk

To open the trunk, press from inside the vehicle or press on the Remote Keyless Entry (RKE) transmitter, or press the touch pad on the rear of the trunk above the license plate. See Remote Keyless Entry (RKE) System Operation on page 2-3 and Trunk on page 2-14.



If the warning light comes on, and StabiliTrak, press and hold stop as soon as possible and inflate Maintenance button on the center stack, the tires to the recommended pressure shown on the Tire and until come on in the. See Rear Seats on page 310. Keys Warning Leaving children in a vehicle with a Remote Keyless Entry RKE transmitter is dangerous and children or others could be seriously injured or killed. If the Unlock Press to unlock the Remote Start If equipped, vehicle has this feature, there will be driver door or all doors depending press and release and then a button on the outside front door on the personalization settings. Only RKE transmitters programmed to the vehicle will work. If a transmitter is lost or stolen, a replacement can be purchased and programmed through your dealer. The vehicle must be 3. Repeat Step 2 two additional off and all transmitters to be times. After the third time all transmitter pocket and press programmed must be with you. The storage REMOTE KEY WAS DETECTED. 3. With the vehicle in P Park or area will need to be opened to PLACE KEY IN TRANSMITTER N Neutral, press the brake access the transmitter pocket. POCKET. If equipped, this feature allows the Other conditions can affect the engine to be started from outside performance of the transmitter. See the vehicle. A child can be overcome by extreme heat and can suffer permanent injuries or even death from heat stroke. Pull once on the door handle to unlock the door and again to open the door. Press the power door lock switch to lock or unlock all doors automatically. The vehicle is programmed so that and only the driver door will unlock. See Vehicle also disabled. See Power Windows Personalization on page 548. See Climate Control Systems in the Index. Use the handle to assist in closing If the vehicle is equipped with the trunk. This handle will glow features; however, they do not make following exposure to light. Pull the the vehicle impossible to steal. <http://domesticsolutionsagency.com/userfiles/dgs-200-moultrie-manual.xml>

Canceling a Remote Start

To cancel a remote start, do any of the following:

- Press and hold until the parking lamps turn off.
- Turn on the hazard warning flashers.
- Turn the vehicle on and then off. See Remote Vehicle Start on page 2-9.

Door Locks

To lock or unlock a door manually:

- Use the key in the driver door. The key cylinder is covered by a cap. See Door Locks on page 2-10.
- From the inside, to lock a door push down on the door lock knob on top of the door. To unlock a door, pull once on the door handle to unlock it, and again to open it.

Power Door Locks

From the inside, press or on the RKE transmitter. See Remote Keyless Entry (RKE) System Operation on page 2-3.

From the outside, if the vehicle is equipped with Keyless Access, press the button on the door handle when the Remote Keyless Entry (RKE) transmitter is within range to

unlock it. See Remote Keyless Entry (RKE) System Operation on page 2-3.

Trunk

To open the trunk, press from inside the vehicle or press on the Remote Keyless Entry (RKE) transmitter, or press the touch pad on the rear of the trunk above the license plate. See Remote Keyless Entry (RKE) System Operation on page 2-3 and Trunk on page 2-14.



The vehicle alarm system will not Disarming the Alarm System A door, the hood, or the trunk arm if the doors are locked with To disarm the alarm system or turn is open. Up to eight Convex Mirrors transmitters can be programmed for the vehicle. To program additional Caution transmitters, see Programming Transmitters to the Vehicle under A convex mirror can make things, Remote Keyless Entry RKE The light will Interior Rearview Mirrors exterior automatic dimming mirror illuminate the ground when the door Adjust the rearview mirror for a clear that will automatically adjust for the is

opened. This may result in a Warning pulsing sound when either rear window is down and the front window is up. Never leave a child, a helpless animal, or a pet alone in a vehicle, especially with the windows up. To reduce the sound, open either a front window especially with the windows. The vehicle may be equipped with a remote venting window feature. As you approach the vehicle, Sun Visors press. When the vehicle is shifted into D Drive, the sunshade will not automatically extend. Press and release the switch to extend the sunshade. The front or rear of the sunshade will automatically open the sunshade to the desired position. For vehicles equipped with a sunroof, do not plug the water drainage system. Periodically open the sunroof and remove any obstacles or loose debris. Do not drive until the head restraints for all occupants are installed and adjusted properly. The height of the head restraint can be adjusted. Pull the head restraint up and push it rearward until it locks into place. Raise or lower the front part of the seat cushion by moving the front of the control up or down. Raise or lower the seat by moving the rear of the control up or down. Even when buckled up, the safety belts cannot do their job. The shoulder belt will not be against your body.

Instead, it will be in front of you. If you cannot feel temperature change or pain to the skin, the seat heater may cause burns. A ventilated seat has a fan that pulls or pushes air through the seat. During a remote start, the heated or ventilated seats, if equipped, can be turned on either side of the vehicle. A red tab near the seatback lever retracts when the seatback is locked in place. See the Warning under Heated and Ventilated Front Seats on page 39. That is why wearing seat belts makes such good sense. Do not allow passengers to ride in any area of the vehicle that is not equipped with seat belts. Will I be trapped in the vehicle. Do not let it get twisted. The lap/shoulder belt may lock if the following instructions explain you pull the belt across you very how to wear a lap/shoulder belt. See and not falling off of it. The belt Height Adjuster should be close to, but not later in this section for use and. If there is one guide for each outside desired position, try to move it down pretensioners activate in a crash, passenger position in the rear seat. These parts of the body are best able to take belt restraining forces. 2. Place the guide over the belt, 3. Be sure that the belt is not twisted and insert the two edges of the twisted and it lies flat. To help make sure the time of the crash. In some crashes seriously injured or killed. Do not Children who are up against, safety belts are the only restraint. Driver Side Shown, Passenger Side Shown. The driver knee airbag is below the steering column. The front outboard passenger knee airbag is below the seat-mounted side impact beam. The driver frontal airbag is in the glove box. The path of an inflating airbag must be kept clear.

Front Suspension.pdf

Installation (With J64) Tire and Wheel Removal and Installation (With J55)

3. Disconnect any harnesses or retainers secured to the stabilizer shaft link. Note any attaching points to aid in installation.

| | |
|---|---|
| 1 | Stabilizer Shaft Link Nut (Qty: 2) CAUTION: Refer to Fastener Caution . |
| 2 | Tighten 65 N.m (48 lb ft) Stabilizer Shaft Link |

FRONT WHEEL BEARING AND HUB REPLACEMENT (GNB)




Fig. 3: Front Wheel Bearing And Hub Assembly, Front Brake Shield & Bolts (GNB)
Courtesy of GENERAL MOTORS COMPANY

| Callout | Component Name |
|---|--|
| Preliminary Procedure | |
| 1. Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle . 2. Remove the front suspension strut yoke. Refer to Front Suspension Strut Yoke Replacement (GNB) . | |
| | Front Wheel Bearing and Hub Assembly Bolt (Qty: 3) CAUTION: Refer to Fastener Caution . CAUTION: |

5 / 57

<http://www.raumboerse-luzern.ch/mieten/3m-steri-vac-5xl-service-manual>

There may problems following an airbag appears to be drivable after a be some smoke and dust coming deployment, you should seek moderate crash, there may be. The service manual The passenger sensing system for the vehicle covers the need works with sensors that are part of to replace other parts. The sensors are designed to detect The vehicle has a crash sensing the presence of a properly seated and diagnostic module which. A child in a rearfacing child Secure rearfacing child restraints When the passenger sensing restraint can be seriously injured in a rear seat, even if the system has turned off the front or killed if the passenger frontal. An heaters, or seat massagers. Also adultsized occupant should not remove laptops, or other ride in the front outboard. This For up to 10 seconds after the instrument panel, any of the airbag could either prevent proper vehicle is turned off and the. See Parts after a Crash The airbag system does not need your dealer for service. If yes, continue. If no, weight and height limitations for that Older Children return to the booster seat. The belt force would then be thrown out of the vehicle. Older applied right on the abdomen. Neither Everyone in a vehicle needs the vehicles safety belt system nor protection. This includes infants and its airbag system is designed all other children. Selection of a particular Warning Continued Warning restraint should take into consideration not only the childs seat, always move the front To reduce the risk of neck and weight, height, and age but also passenger seat as far back as it head injury during a crash, infants whether or not the restraint will will go. Instead, it may settle up around the childs abdomen. Warning When securing an addon child restraint, refer to the instructions A child can be seriously injured or that come with the restraint which killed in a crash if the child. For CPST a rear seating position.

<http://cootowlaw.com/images/briggs-and-stratton-engine-workshop-manuals.pdf>

Front Suspension.pdf

Installation (With J64) Tire and Wheel Removal and Installation (With J55)

3. Disconnect any harnesses or retainers secured to the stabilizer shaft link. Note any attaching points to aid in installation.

| | |
|---|---|
| 1 | Stabilizer Shaft Link Nut (Qty: 2) CAUTION: Refer to Fastener Caution . |
| 2 | Tighten 65 N.m (48 lb ft) Stabilizer Shaft Link |

FRONT WHEEL BEARING AND HUB REPLACEMENT (GNB)




Fig. 3: Front Wheel Bearing And Hub Assembly, Front Brake Shield & Bolts (GNB)
Courtesy of GENERAL MOTORS COMPANY

| Callout | Component Name |
|---|--|
| Front Wheel Bearing and Hub Replacement (GNB) | |
| Preliminary Procedure | |
| 1. Raise and support the vehicle. Refer to Lifting and Jacking the Vehicle . 2. Remove the front suspension strut yoke. Refer to Front Suspension Strut Yoke Replacement (GNB) . | |
| | Front Wheel Bearing and Hub Assembly Bolt (Qty: 3) CAUTION: Refer to Fastener Caution . CAUTION: |

5 / 57

Even if the passenger sensing availability in Canada, check with Never put a rearfacing child seat in system has turned off the right. A child restraint must never be installed using only the top tether and anchor. Anchor Locations Either will have a single attachment 2 to secure the top tether to the anchor. Some child restraints that have a To assist in locating the lower top tether are designed for use with. If the position you are using If the position you are using has an adjustable headrest has an adjustable headrest or head restraint and you. When securing a child restraint in a Warning rear seating position, study the If the child restraint does not have. The child restraint instructions will show you how. 4. Pull the shoulder belt all the way 5. To tighten the belt, push down out of the retractor to set the on the child restraint, pull the lock. A rear restraint can be seriously injured tether. See Warning Continued position without a top tether anchor Passenger Airbag Status if a national or local law requires Indicator on page 518. Secure rearfacing child restraints that the top tether be anchored, or if 2. To check, if necessary. Pull up on the lever to access the panel to open. There is a USB port If equipped, there is a compact disc storage area. There are cupholders in the center There is a power outlet inside. To console. Push and release on the close, push the cover again and passenger side of the cover to Push the button and lift to access release. The net is attached to the cargo Cargo TieDowns tiedowns. Put small loads behind the net. It can also be positioned into an envelope to hold smaller items inside. Favorite Press to go to the next Press to mute or unmute the or previous favorite when listening Horn infotainment system when not on. Turn the wipers are on LO, HI, or INT, they band on the wiper lever to adjust the will immediately stop.

<http://cornerstonedurham.com/images/briggs-and-stratton-engines-manual.pdf>



See Washer Fluid operate for a certain number of When using an automatic car wash, on page 1022 for information on miles or degrees of turn before move the windshield wiper lever to filling the windshield washer fluid. To set the date Time If auto timing is set, the time 1. Press the SETTINGS screen To set the time displayed on the clock may not button and press Time and Date. Often gauges and warning Holding a cigarette lighter in while lights work together to indicate a Indicators it is heating does not let the problem with the vehicle. Performance Configuration Balanced Configuration The Performance configuration has The Balanced configuration has two interactive display zones one in three interactive display zones one the center of the speedometer and in the center of each of the gauges. If there is side of the steering wheel to move an active call, mute the phone or The cluster can display information between the different display zones switch to handset operation. If the vehicle needs a The tachometer displays the engine change the configuration of the new cluster installed, the new speed in revolutions per uplevel cluster. There is an arrow near the fuel gauge pointing to the side of the vehicle the fuel door is on. None of these Temperature Gauge show a problem with the fuel gauge At the service station, the fuel pump shuts off before the gauge reads full. It takes a little more or less fuel to fill up than the gauge indicated. Then the light stays their safety belt. Then the light stays temperature of the vehicles engine. This cycle may continue several This cycle continues several times if While driving under normal. The Warning passenger airbag status indicator is This light shows if there is an in the overhead console. If the airbag readiness light stays electrical problem with the airbag on after the vehicle is started or system. It should and knee airbag.

If the airbag readiness light ever For vehicles with a reconfigurable If the word ON or the on symbol is. Being aware of the light Modifications made to the engine, can prevent more serious damage A computer system called OBD II transmission, exhaust, intake, to the vehicle. See your dealer for Depending on where you live, your assistance in verifying proper The vehicle brake system consists vehicle may be required to operation of the malfunction of two hydraulic circuits. The brake system might not be system. If the light comes on while driving, stop as soon as it is safely possible and turn off the vehicle. Adjust driving accordingly. Stability Control on page 929. Driving Stability Control on page 929. This light should come on briefly as engine is started. See on and ready, and turns green when Exterior Lamp Controls on page 61. When an item is Driver Information cluster. Press to go back to the selected, a checkmark will previous menu. Clean the inside of the windshield to Messages displayed on the DIC Polarized sunglasses are remove any dirt or film that could indicate the status of the vehicle or not worn. Some This message is displayed if you BATTERY SAVER ACTIVE features can be disabled while in attempt to release the Electric this mode, including Remote. Take the vehicle to your attempting to activate Adaptive Adaptive Cruise Control ACC is dealer for service. Collision Preparation feature. Some lastsecond automatic braking 24 GHz RADARS OFF This message may also be capability is still provided with the displayed if there is a problem with. The vehicle does not need service. Restart the Traction Control System TCS has This message displays when there vehicle and check for the message been turned on. This message is

displayed if there is a problem with the pushbutton start a problem with the power steering.
SERVICE TRANSMISSION WASHER FLUID LOW ADD Stop the vehicle and let it idle to allow the transmission to cool.

<http://bubblesoflove.net/wp-content/plugins/formcraft/file-upload/server/content/files/1626f856b86c00---bose-321-repair-manual.pdf>

This FLUID This message displays if there is a message clears when the fluid problem with the transmission. See menu and the following may be Clock on page 55. displayed SETTINGS Press Language and the following. On some vehicles Delayed Door Lock Remote Lock Feedback select Off, Normal Sensitivity, When on, this feature will delay the This allows selection of what type of or Low Sensitivity.To override the feedback is given when locking the delay, press the power door lock vehicle with the RKE transmitter. Display, Rear Park Assist Symbols, button on the driver door to unlock Guidance Lines, and Rear Cross Select Cancel or Continue. These park outside directly in line with and System instructions refer to a garage door facing the garage door opener opener, but can be used for other receiver. Do not release the button. 2. The indicator light will begin to flash after 20 seconds. Without releasing the button, proceed with Step 1 under Programming the Universal Remote System. Keep this area of the windshield Parking Lamps Turns on the clear of debris to allow for best parking lamps including all lamps, system performance. When the wipers are Curve Lighting Hazard Warning Flashers not operating, these lamps turn off.Illumination Control If after signaling a turn or lane change, the arrow flashes rapidly or does not come on, a signal bulb may be burned out. The instrument console.See Vehicle Locator Lights under Vehicle Personalization on Entry Lighting page 548. The headlamps, taillamps, backup Exit Lighting lamps, license plate lamps, outside mirror lamps, exterior door handle The headlamps, taillamps, parking lamps, dome lamps, and most of lamps, outside mirror lamps, license the interior lights turn on briefly at. If some interior lamps are left on and the ignition is turned off, the battery rundown protection system automatically turns the lamp off after some time. Exterior Lighting Battery Saver The exterior lamps turn off about.

To adjust the windshield of fog or frost more press the desired air delivery mode sensitivity of the air quality sensor, quickly. See air conditioner. If the climate control Climate and Air Quality under Do not try to clear frost or other system does not detect possible Vehicle Personalization on material from the inside of the. The control system, the settings can be system uses the driver s previous adjusted with the rear climate settings to heat or cool the inside of. The air conditioning Passenger Compartment vehicle more effectively.Taking your eyes off the road too are important factors in helping to Focus on the task of driving.This provides normally but do not pump the held against that position for an maximum control and stability. Ease your foot off the Loss of Control Driving on Wet Roads accelerator pedal and steer the way you want the vehicle to go. Besides slowing down, other wet Check the rearview mirror and weather driving tips include Flowing or rushing water creates vehicle instruments often. Warning Continued signs falling rocks area, winding If you accelerate too fast, the drive roads, long grades, passing or wheels will spin and polish the could result in a loss of braking. Blizzard Conditions vehicle and set the fan speed cannot be seen or smelled. It can to the highest setting. See cause unconsciousness and even Being stuck in snow can be a Climate Control Systems. With the driver Rating GAWR for the front and Warning Continued door open, you will find the label rear axle; see Certification attached below the door lock Label later in this section.The combined weight of the driver, passengers, and cargo should never exceed the vehicles capacity weight.Never exceed See Steps for Determining packages, or anything else the GVWR for the vehicle, or the. Plugging the cord into an When the engine starts, let go of ungrounded outlet could cause an the button and the accelerator. See These vehicle accessories can be engine is running.

If you have left Electric Parking Brake on used for up to 10 minutes after the page 927. If you can, it means that Shifting out of Park If you still are unable to shift out of the shift lever was not fully

locked P Park This vehicle is equipped with an into P Park. If you cannot shift out of It is dangerous to get out of the P Park, ease pressure on the shift vehicle if the shift lever is not fully lever, then push the shift lever all in P Park with the parking brake. N Neutral with the engine or does not shift gears, the N Neutral In this position, the. Tap the left Drive Systems control to downshift, and the right Tap Shift control to upshift. A Driver AllWheel Drive Information Center DIC message indicates the gear the vehicle is in. If equipped, this feature transfers torque to the rear wheels as When accelerating the vehicle from. Always becomes necessary to slam on the leave enough room up ahead to brakes and continue braking to stop, even with ABS. Antilock Brake avoid a sudden obstacle, a Using ABS. See Electric EPB is fully applied. If the red Parking Brake Light on page 523 parking brake status light flashes and Service Electric Parking Brake. If either light Brake Assist the EPB in some situations when stays on after release is attempted, This vehicle has a brake assist the vehicle is not moving. This is see your dealer. The Traction and release the button. The more control. This setting provides Off Light displays in the Traction Off Light. You cornering hard or completing a may hear the air compressor Warning maneuver, such as a lane change. A white indicator cruise control without erasing the limit wheel spin while using cruise appears in the instrument cluster set speed from memory. SET down to the second desired speed and then the brakes For each press, the vehicle. If no vehicle is detected in or shortly following the release to your path, ACC works like regular There are three ways to end cruise override cruise, briefly applying the cruise control.

This is the vehicle speed and activate ACC or to decrease when no vehicle is detected in vehicle speed if ACC is already its path. See When a slower moving vehicle is driving conditions. The electric parking brake status light will turn Leaving the vehicle without The ACC will not automatically on. See Electric Parking Brake on placing it in P Park can be apply the brakes if your foot is page 927. It could On curves, ACC may respond to accelerate to the set speed. This system detects traffic. Failure to use proper care objects coming from up to 20 m before backing may result in 65 ft from the left or right side of injury, death, or vehicle damage. If the The Backing Warning System brake pedal is not pressed within only operates at speeds greater. The system The APA system does not need of the parking maneuver. Depending cannot detect whether it is a legal service. The APA system may require a barrels, or other objects. Be ready short period of driving along curves FCA detects vehicles within a to take action and apply the. Vehicles may not be Collision Alert Tailgating Alert detected on curves, highway exit ramps, or hills; or due to poor visibility. FCA will not detect another vehicle ahead until it is completely in the driving lane. Warning With HeadUp Display The vehicleahead indicator will. The range of Washing the Vehicle under selectable alert timing may not be Exterior Care on page 1082.Warning Continued pedal movement during this time is See Forward Collision Alert FCA normal and the brake pedal should System on page 950. Complete attention is always continue to be applied as needed. If this personalization. See the Auto SBZA does not alert the driver to happens, Automatic Braking will Collision Preparation portion of vehicles rapidly approaching. SBZA can be disabled through This indicates it may be unsafe to vehicle personalization.

The system may light up reason other than the driver turning right side of the seat, depending on due to guardrails, signs, trees, it off, the Side Blind Zone Alert On the lane departure direction. If the Warning octane rating is less than 87, an Use of the recommended fuel is an audible knocking noise, commonly LDW does not provide a warning important part of the proper referred to as spark knock, might be to help avoid a crash, unless it maintenance of this vehicle. Countries It is available at your dealer. Keep children away from the If planning to drive in countries fuel pump and never let Filling the Tank outside the U.S. Do not Filling the Tank with a Portable top off or overfill the tank and wait a Gas Can few seconds before removing the If the vehicle runs out of fuel and nozzle. General Towing Place the nozzle inside the fill opening of the container Information Filling a Portable Fuel before dispensing fuel, and Container Only use towing equipment that has keep it in contact with the fill. The damage to the engine, axle, combination you are driving is When towing a trailer, exhaust or

other parts. Shift Caution Continued the transmission to a lower gear if More passing distance is needed the transmission shifts too often when towing a trailer. The The vehicle could be damaged. Then operation are automatic apply the parking brake and shift transmission fluid, engine oil, axle into P Park. It is a good idea to 5. Weight of the Trailer Tongue For example, speed, altitude, road The tongue load 1 of any trailer is grades, outside temperature, and an important weight to measure how much the vehicle is used to pull because it affects the total gross a trailer are all important. If so, brakes Be sure to read and follow Be sure the vehicles tires are seal the holes when the hitch is the instructions for the trailer brakes. Always check with your dealer before adding electrical equipment.

Hood Before attempting to do your own To open the hood service work, see Servicing the Airbag Equipped Vehicle on page 333. Keep a record with all parts receipts and list the mileage and the date of any service work performed. Battery on page 1025 Battery Engine Cover page 1013. Cover not Shown. 2. Power Steering Fluid Reservoir 11. See Battery Cover not Shown. Power Steering Fluid LF3 and See Jump Starting on LFX with AWD on page 1021 page 1076. It is a good idea to check the engine oil level at each fuel fill. In order to Engine Oil get an accurate reading, the vehicle must be on level ground. See the Caution specification. See Specification manufacturers warnings about the earlier in this section. If a leak See Maintenance Schedule on occurs, take the vehicle to the page 114. Keep hands, clothing, and tools away from any underhood electric fan. If there is a coolant. If using this mixture, Using coolant other than problem with engine overheating, nothing else needs to be added. Steam and scalding liquids from a tank pressure cap and upper 5. Running the engine without See Engine Cooling System coolant may cause damage or a Messages on page 539. fire. Vehicle damage would not be If the decision is made not to lift the covered by the vehicle warranty. If the warning continues, pull over, Warning Continued stop, and park the vehicle Tows a trailer. right away. Wait until there is no sign of If the overheat warning is displayed If there is no sign of steam, idle the with no sign of steam steam or coolant before you open. Fluid instrument cluster, to indicate the It is not necessary to regularly vehicle has entered overheated check power steering fluid unless engine protection operating mode. Add washer fluid until What to Use the tank is full. See Engine expansion if freezing occurs, Compartment Overview on When adding windshield washer which could damage the tank page 105 for reservoir location.

This could be a sign change in many other ways if the Caution that brake service might be wrong replacement brake parts are required. installed. Continuing to drive with wornout Brake Adjustment brake pads could result in costly Brake Fluid brake repair. Have the brake on. See Brake System Warning Using the wrong fluid can hydraulic system fixed, since a Light on page 522. If required, have the transfer case Refer to the replacement number serviced by your dealer. Warning shown on the original battery label when a new battery is needed. See Starter Switch Check Batteries have acid that can burn Engine Compartment Overview on. Warning Continued gear. The vehicle should start See Electric Parking Brake on only in P Park or N Neutral. page 927. of the vehicle in case it begins to If the vehicle starts in any other Be ready to apply the regular roll. Headlamp aim has been preset and For the proper type of replacement For replacement of any LED lighting should need no further adjustment. Have the Overload protected from short circuits by a headlamp wiring checked right away. The vehicle may not be equipped JCase Usage with all of the fuses, relays, and Fuses Caution features shown. Wiper Control Fuses Usage The instrument panel fuse block is. The vehicle may not be equipped Fuse Usage with all of the fuses, relays, and Number features shown. Leveling Fuse Usage. See Worn or old tires can Vehicle Load Limits on cause a crash. If the tread Every new GM vehicle has page 910. HighSpeed Operation on speed rating as the original See Winter Tires on page 1039. See the DOT Tire Date of Tire Size illustration later in this Manufacture The last four Useful information about a tire is section. The tire manufactured date. The maximum pressure needed to equipment tires designed to letter P as the first character in. HighSpeed Operation Use a good quality pockettype gauge to check tire pressure.

<https://congviendisan.vn/vi/3m-steri-vac-5xl-service-manual>